



MALCO MARINE · MALCO / PRESTA · COMPOUNDS & POLISHES

CHROMA ULTRA POLISH

FINISHING POLISH FOR GEL COAT AND PAINTED SURFACES

SKU

133532

32 OZ.

128 OZ.

133501

: Presta Marine Ultra Polish works best when machine-applied. This cleaner/polish removes minor surface imperfections and oxidation from new or aged marine paint and gel coat. With no waxes, scratch-fillers or silicones that hide defects, Ultra Polish creates an extremely high gloss finish.

PERFORMANCE

ROLE	Marine chemical · Compounds & Polishes
CUT / SANDING	P3000 or P5000 on softer glamour clear coats and gel coats (TDS)
APPEARANCE	Liquid · Green. (SDS)
DENSITY / SG	Not available. (SDS)
ODOR	Watermelon. (SDS)
VOC	VOC Compliant ☑ Eco-fr (TDS)

APPLICATION & PHYSICAL

BUFFING SPEED	1400 to 2000 rpm with wool or 1200 to 1800 rpm with foam, depending on surface s (TDS)
FLASH POINT	145.0 °F (62.8 °C) (SDS)
TRANSPORT	DOT Not regulated (SDS)
MDSC SIZES	32 oz. (133532), 128 oz. (133501)
FEATURES (TDS)	Reliable polish ☑ Cleans and removes minor surface imperfections & oxidation; East to work with formula ☑ Leaves no hard-to-remove residue; Contains no fillers, waxes or silicones ☑ Leaves deep, high-gloss finish; VOC Compliant ☑ Eco-friendly

OVERVIEW

: Presta Marine Ultra Polish works best when machine-applied. This cleaner/polish removes minor surface imperfections and oxidation from new or aged marine paint and gel coat. With no waxes, scratch-fillers or silicones that hide defects, Ultra Polish creates an extremely high gloss finish that won't wash away. Ultra Polish works best after compounding.

DIRECTIONS

- 1 Make sure that the surface is clean, cool and dry.
- 2 Shake product well and apply a 1" (25 mm) dab for a 2'x 2' (.6m x .6m) area.
- 3 Buff at 1400 to 2000 rpm with wool or 1200 to 1800 rpm with foam, depending on surface softness. Apply even pressure.
- 4 Buff front to back and side to side allowing Ultra Polish to flash off and create a high gloss shine.
- 5 Always ensure finishing strokes are front to back.
- 6 If product dries too quickly, mist with Express Detail (#166622) or water.

SAFETY SNAPSHOT

WARNING

Serious eye damage/eye irritation Category 2A; Flammable liquids Category 4; Acute toxicity, oral Category 5; Acute toxicity, inhalation Category 5; Specific target organ toxicity, repeated Category 2

APPEARANCE	Liquid.
PH / DENS.	Not available.
FLASH POINT	145.0 °F (62.8 °C)
TRANSPORT	DOT Not regulated

Manufacturer SDS — Malco / Presta Chroma Ultra Polish →

SOURCES

1. Manufacturer tech data / product information — [https://www.prestaproducts.com/images/MediaGallery/Presta Marine Tech Data Sheet Ultra Polish .pdf](https://www.prestaproducts.com/images/MediaGallery/Presta%20Marine%20Tech%20Data%20Sheet%20Ultra%20Polish.pdf)
2. Manufacturer SDS — [https://www.prestaproducts.com/images/MediaGallery/SDS US-1335-2018-5-3_English.pdf](https://www.prestaproducts.com/images/MediaGallery/SDS%20US-1335-2018-5-3_English.pdf)
3. Manufacturer product page — https://www.prestaproducts.com/ULTRA_POLISH-details.aspx
4. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailssupply.com/products/presta-chroma-ultra-polish>
5. Mapping note — MDSC titles use Malco Marine Chroma branding; manufacturer Presta page still lists Ultra Cutting Creme / Ultra Polish part families.