



MALCO MARINE · MALCO / PRESTA · COMPOUNDS & POLISHES

GEL COAT COMPOUND

VOC-COMPLIANT WATER-BASED MARINE GEL COAT COMPOUND

SKU

138532

32 OZ.

128 OZ.

138501

: Presta Marine Gel Coat Compound is the perfect compound for marine and industrial applications. Gel Coat Compound is a VOC compliant, water-based product. This easy-to-use and easy-to-clean up formula significantly reduces manufacturing and buffing time. It removes P1000 or fin

PERFORMANCE

ROLE	Marine chemical · Compounds & Polishes
CUT / SANDING	P1000 or finer sand scratches and medium to light oxidation (TDS)
PH	8.8 (SDS)
APPEARANCE	Viscous. Cream. · Liquid. · White. (SDS)
DENSITY / SG	Not available. (SDS)
ODOR	Vanilla (SDS)
VOC	VOC compliant, water-based product (TDS)

APPLICATION & PHYSICAL

BUFFING SPEED	a speed between 1800 to 2600 rpm (TDS)
FLASH POINT	190.0 °F (87.8 °C) (SDS)
TRANSPORT	DOT Not regulated (SDS)
MDSC SIZES	32 oz. (138532), 128 oz. (138501)
FEATURES (TDS)	VOC Compliant & shop safe ☑ Eco-friendly; Water-based emulsion formula ☑ Easy to use; Contains no fillers, waxes or silicones ☑ Leaves deep, high-gloss finish; Cuts fast ☑ Removes P1000 and finer sand scratches and

OVERVIEW

: Presta Marine Gel Coat Compound is the perfect compound for marine and industrial applications. Gel Coat Compound is a VOC compliant, water-based product. This easy-to-use and easy-to-clean up formula significantly reduces manufacturing and buffing time. It removes P1000 or finer sand scratches and medium to light oxidation. Gel Coat Compound quickly leaves a deep high-gloss finish without the use of waxes, silicones or fillers.

DIRECTIONS

1. Shake well before using. Do not apply in sunlight or on warm surfaces.
2. Apply a 2" dab of Gel Coat Compound for a 2' x 2' (.6m x .6m) section and spread with the cutting pad.
3. Buff at a speed between 1800 to 2600 rpm. (

SAFETY SNAPSHOT

WARNING

Serious eye damage/eye irritation Category 2A; Flammable liquids Category 4; Acute toxicity, oral Category 5; Acute toxicity, inhalation Category 5; Specific target organ toxicity, repeated Category 2; Combustible liquid. May be harmful if swallowed. Causes serious eye irritation. May be harmful if

APPEARANCE	Viscous. Cream.
PH / DENS.	8.8 · Not available.
FLASH POINT	190.0 °F (87.8 °C)
TRANSPORT	DOT Not regulated

Manufacturer SDS — Malco / Presta Gel Coat Compound →

SOURCES

1. Manufacturer tech data / product information — <https://www.prestaproducts.com/images/MediaGallery/Presta Marine Tech Data Sheet Gel Coat .pdf>
2. Manufacturer SDS — https://www.prestaproducts.com/images/MediaGallery/SDS US-1385-2018-5-16_English.pdf
3. Manufacturer product page — https://www.prestaproducts.com/GEL_COAT-details.aspx
4. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailssupply.com/products/presta-gel-coat-compound>