



MALCO MARINE · MALCO PRODUCTS · SEALANTS

MALCO MARINE SHIELDPRO UV CREME WAX

UV CRÈME WAX · PART FAMILY 1661

SKU

166132

32 OZ.

128 OZ.

166101

Provides long-lasting shine and UV protection on fiberglass, gelcoat, and painted marine finishes in one step. Polishing agents and waxes combine with aminofunctional silicones, dual-functional UV absorber, silicone resin, and polymers for gloss and protection against salt, corrosion, and UV.

PERFORMANCE

ROLE	One-step UV crème wax (TDS)
SURFACES	Gel coat, fiberglass, and painted marine finishes (TDS)
DURABILITY	Lasts up to 6 months with UV protection (TDS)
PROTECTION	Against salt, oxidation, and the sun's UV rays (TDS)
APPEARANCE	Cream · Yellow · Banana odor (SDS)
VOC	14% by weight (SDS)
FLASH POINT	>145.0 °F / >62.8 °C (SDS)

APPLICATION & PHYSICAL

METHOD	Hand, DA, or buffer; apply thin even film; haze then polish off (TDS)
PREP WASH	Wash first with HydroFoam Concentrated Boat Wash (1620) (TDS)
CONDITIONS	Cool, dry surface (TDS)
TRANSPORT	Not regulated as dangerous goods — DOT/IATA/IMDG (SDS §14)
PHYSICAL HAZARDS	Flammable liquids Category 4 (SDS)
HEALTH HAZARDS	Acute tox. oral Cat. 5; Eye Cat. 2B; STOT RE Cat. 2 (SDS)

OVERVIEW

Provides long-lasting shine and UV protection on fiberglass, gelcoat, and painted marine finishes in one step. Polishing agents and waxes combine with aminofunctional silicones, dual-functional UV absorber, silicone resin, and polymers for gloss and protection against salt, corrosion, and UV.

DIRECTIONS

1. Wash boat thoroughly with HydroFoam Concentrated Boat Wash (1620) to remove heavy dirt and grime.
2. Ensure surface is cool and dry. Shake well before using.
3. Apply with a soft cloth or wax applicator pad and spread to a thin, even film, section by section or over the entire surface.
4. Allow wax to dry to a light haze.
5. Polish off by hand with a soft clean microfiber or with a random orbital polisher.

SAFETY SNAPSHOT

⚠ DANGER

Flam. liq. Cat. 4 · Acute tox. oral Cat. 5 · Eye irritation Cat. 2B · STOT RE Cat. 2 · Combustible liquid

APPEARANCE	Cream · Yellow
ODOR	Banana
VOC	14% by weight
FLASH POINT	>145 °F (>62.8 °C)
TRANSPORT	Not regulated (DOT/IATA/IMDG)

[Manufacturer SDS — ShieldPro UV Creme Wax →](#)

SOURCES

1. Manufacturer tech data / product information — https://cdn.shopify.com/s/files/1/0757/6377/7832/files/1661_ShieldPro_UV_Creme_Wax_Tech_Data_Sheet_Draft_08272025.pdf?v=1764620032
2. Manufacturer product page — <https://malcomarine.com/products/shieldpro>
3. Manufacturer SDS (ShieldPro UV Creme Wax) — https://cdn.shopify.com/s/files/1/0757/6377/7832/files/SDS_US_1661_Shieldpro_UV_Creme_Wax_English_current.pdf
4. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailssupply.com/products/malco-marine-shieldpro-uv-creme-wax>
5. Omissions — pH and relative density not published on SDS