



FLEX · FLEX POWER TOOLS · POLISHERS

PE 14-2 150

POLISHFLEX CORDED ROTARY · VARIABLE SPEED

SKU

373.923

DEFAULT TITLE

High-torque corded rotary polisher with wide speed range for pads from small to 200 mm discs.

PERFORMANCE

POWER CONSUMPTION	1,400 W (mfr)
POWER OUTPUT	880 W (mfr)
MAX. SUPPORT PLATE	150 mm (mfr)
MAX. POLISHING DISC	200 mm (mfr)
NO-LOAD SPEED	380 – 2,100 rpm (mfr)
WEIGHT	2.3 kg (mfr)

APPLICATION & PHYSICAL

CABLE	4.0 m PUR (mfr)
DIMENSIONS	405 × 84 × 117 mm (mfr)
ELECTRONICS	Microprocessor: stepless speed, constant speed, overload, restart protection, temperature monitoring (mfr)
STARTING SPEED	Setting 1 ≈ 380 rpm for gentle start (mfr)

OVERVIEW

FLEX PE 14-2 150 POLISHFLEX rotary polisher. Planetary + angular gearing for low noise, flat gear head, and SoftGrip hood for precise control.

DIRECTIONS

- 1 Mount an M14 rotary backing pad and appropriate pad.
- 2 Start at setting 1 for a gentle launch; raise speed for cutting.
- 3 Keep pad flat; use spindle lock only when changing discs with power off.
- 4 Unplug before pad changes or storage.

SAFETY SNAPSHOT

CORDED POWER TOOL — EYE/HEARING PROTECTION

Follow FLEX operator manual. Unplug before pad changes.

WEIGHT	2.3 kg
CABLE	4.0 m PUR

Manufacturer SDS URL not retrieved for this article.

SOURCES

1. Manufacturer tech data / product information — <https://www.flex-tools.com/en-gb/products/polishers/rotary-polishers/pe-14-2-150-230-bs>
2. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailssupply.com/products/flex-pe14-2-150-rotary-polisher-h>
3. Mapping note — EU product page lists 230 V; voltage omitted for US retail SKU.
4. Omissions — Mains voltage omitted — EU page lists 230 V; confirm US article rating.; SDS not retrieved.