



KOCH CHEMIE · KOCH-CHEMIE · COMPOUNDS & POLISHES

MICRO CUT M3.02

ANTI-HOLOGRAM FINISHING POLISH

SKU

403250US

250ML

1L

403001US

Micro Cut M3.02 is the latest generation machine micro-polish for the permanent removal of streaks, holograms, fine scratches and sanding marks to P3000 grain size on all paint systems (including scratch-resistant). Through the use of highly specialised, extremely homogenous abrasive bodies, a brilliant permanent hi...

PERFORMANCE

ROLE	Polish
SURFACES / AREAS	Paintwork of cars, commercial vehicles, motor cycles, etc.
CUT	3.2 (PI)
GLOSS LEVEL	9.0 (PI)
PH	8 (SDS)
APPEARANCE	Grey · Characteristic (SDS)
DENSITY	1.01 g/ml (SDS)

APPLICATION & PHYSICAL

METHOD	For optimum results we recommend using our Micro Cut Pad and an orbital polisher with forced rotation (eg Makita PO5000C, highest speed).
FLASH POINT	>93 °C (SDS)
VOC	~ 12 % (SDS)
TRANSPORT	Not regulated for transport (SDS §14)
WARNINGS (PI)	Shake before using. Before using, check suitability and compatibility. Do not use on hot surfaces. Protect against frost and excessive heat
MDSC SIZES	250ml (403250US), 1L (403001US)

OVERVIEW

Micro Cut M3.02 is the latest generation machine micro-polish for the permanent removal of streaks, holograms, fine scratches and sanding marks to P3000 grain size on all paint systems (including scratch-resistant). Through the use of highly specialised, extremely homogenous abrasive bodies, a brilliant permanent high gloss finish is created under extreme light conditions even on dark and similarly sensitive shades. Holograms and fine scratches are eliminated mechanically and not, which is often the case, covered over. Micro Cut M3.02 is extremely economical, easy to polish and removable without leaving traces. Cut: 3,2 Gloss: 9,0 SDS: mixture not classified as dangerous under CLP.

DIRECTIONS

- For optimum results we recommend using our Micro Cut Pad and an orbital polisher with forced rotation (eg Makita PO5000C, highest speed).
- Alternatively a rotary polisher can be used in combination with our Micro Cut Pad.
- Before use, moisten dried or new pads completely with polish.
- With the machine switched off, apply the polish evenly over the surface to be treated and then polish crosswise with medium pressure until a transparent film appears, ie, until the aluminium oxide in the polish has completely broken down.
- Do not use pads used with this product for other products. For non-scratch and groove-free removal of polish residues we recommend our non-chainstitched Profi microfibre cloth that has been ultrasonically cut.
- PI warnings: Shake before using. Before using, check suitability and compatibility. Do not use on hot surfaces. Protect against frost and excessive heat

SAFETY SNAPSHOT

NOT CLASSIFIED

EUH210-Safety data sheet available on request.

APPEARANCE	Grey · Characteristic
PH / DENS.	8 · 1.01 g/ml
FLASH POINT	>93 °C
TRANSPORT	Not regulated for transport (SDS §14)
VOC	~ 12 %

Manufacturer SDS — Koch-Chemie Micro Cut M3.02 →

SOURCES

1. Manufacturer Product Information (Koch-Chemie) — https://www.koch-chemie.com/pdf/datasheet/Micro_Cut_M302_en.pdf
2. Manufacturer SDS (Koch-Chemie Micro Cut M3.02) — https://media.koch-chemie.com/pdf/SDBL/Micro_Cut_M3-02_Art_403999_403999_0003_EN.pdf
3. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailsupply.com/products/koch-chemie-m3-02-micro-cut-anti-hologram-finishing-polish-1000-ml>