



FLEX · FLEX POWER TOOLS · POLISHERS

XCE 10-8 125

CORDED ECCENTRIC · FORCED ROTATION · 8 MM STROKE

SKU

436.720

DEFAULT TITLE

Corded eccentric polisher with positive-action 8 mm stroke for common surface problems through hologram-free finishing.

PERFORMANCE

POWER CONSUMPTION	1,010 W (mfr)
POWER OUTPUT	590 W (mfr)
MAX. SUPPORT PLATE	150 mm (mfr)
MAX. POLISHING DISC	160 mm (mfr)
POLISHING STROKE	8 mm (mfr)
NO-LOAD SPEED	140 – 440 rpm (mfr)
ORBIT RATE (NO LOAD)	2,900 – 8,600 rpm (mfr)
WEIGHT	2.6 kg (mfr)

APPLICATION & PHYSICAL

CABLE	4.0 m PUR (mfr)
DIMENSIONS	383 × 40 × 140 mm (mfr)
ELECTRONICS	VR microprocessor: constant speed, soft start, restart/overload/temperature protection (mfr)
INCLUDES	Special cushioned hook-and-loop pad 487953 (mfr EU page)

OVERVIEW

FLEX XCE 10-8 125 corded eccentric with forced rotation. 8 mm positive-action stroke for abrasive power without holograms and low heat on temperature-sensitive paints.

DIRECTIONS

- 1 Fit the cushioned special hook-and-loop pad; connect to suitable mains power.
- 2 Use continuous speed trigger for soft start; select speed via VR control.
- 3 Keep the flat gear head close to the surface; work overlapping passes.
- 4 Unplug before pad changes.

SAFETY SNAPSHOT

CORDED POWER TOOL — EYE/HEARING PROTECTION

Follow FLEX operator manual. Unplug before pad changes.

STROKE	8 mm forced
WEIGHT	2.6 kg

Manufacturer SDS URL not retrieved for this article.

SOURCES

1. Manufacturer tech data / product information — <https://www.flex-tools.com/en-gb/products/polishers/random-orbital-polisher/xce-10-8-125-230-bs>
2. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailssupply.com/products/flex-xce-10-8-125-corded-polisher-h>
3. Mapping note — EU product page lists 230 V; voltage omitted for US retail SKU. Power/speed/stroke from manufacturer page.
4. Omissions — Mains voltage omitted — EU page lists 230 V; confirm US article rating.; SDS not retrieved.