



FLEX · FLEX POWER TOOLS · POLISHERS

XFE 15 150 18.0-EC SET

18 V FREE-SPIN DA · 15 MM STROKE

SKU

459.542

DEFAULT TITLE

18 V cordless free-spinning random-orbital polisher with 15 mm stroke for hologram-free finishing and low heat on temperature-sensitive paints.

PERFORMANCE

BATTERY VOLTAGE	18 V (TDS)
BATTERY CAPACITY	2.5 / 5.0 / 8.0 Ah (TDS)
MAX. SUPPORT PLATE	150 mm (TDS)
MAX. POLISHING DISC	160 mm (TDS)
POLISHING STROKE	15 mm (TDS)
NO-LOAD SPEED	2,300 – 3,800 rpm (TDS)
ORBIT RATE (NO LOAD)	4,600 – 7,600 rpm (TDS)
WEIGHT (NO BATTERY)	2.1 kg (TDS)

APPLICATION & PHYSICAL

DIMENSIONS	370 × 85 × 140 mm (TDS)
DRIVE	Free-spinning / hologram-free finishing (TDS)
MOTOR	Brushless with EMS (TDS)
SET NOTE	Manufacturer set lists (2) batteries + charger + pads (TDS) — confirm MDSC kit on catalog page

OVERVIEW

FLEX XFE 15 150 18.0-EC cordless random-orbital polisher. 15 mm free-spinning orbit for efficient finishing with low surface heat — ideal as the finish step after rotary cutting.

DIRECTIONS

- 1 Fit a cushioned hook-and-loop pad and finishing foam.
- 2 Start gently with the continuous speed trigger; raise orbit rate as the pad primes.
- 3 Use light pressure and overlapping passes for hologram-free finish.
- 4 Remove battery before pad changes.

SAFETY SNAPSHOT

CORDLESS POWER TOOL — EYE/HEARING PROTECTION

Follow FLEX operator manual. Use only approved FLEX 18 V batteries and chargers.

PLATFORM	18 V FLEX
STROKE	15 mm free-spin

Manufacturer SDS URL not retrieved for this article.

SOURCES

1. Manufacturer tech data / product information — https://hub.flex-tools.com/_f/9dd/9dd65a3b1fdb3a8e44e4b067c12d4c796838d200/GD_PG_%24KT-DB-%24KP-XCDC-%24PG-465046.pdf
2. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailssupply.com/products/flex-xfe15-150-cordless-orbital-polisher>
3. Mapping note — Manufacturer product data sheet PDF for XFE 15 150 18.0-EC/5.0 Set.
4. Omissions — SDS not applicable / not retrieved for this power tool.