



FLEX · FLEX POWER TOOLS · POLISHERS

XCE 8 150 18-EC (FORCED ROTATION)

18 V GEAR-DRIVEN ECCENTRIC · 8 MM STROKE

SKU

459.55

DEFAULT TITLE

18 V cordless eccentric polisher with forced rotation — 8 mm stroke for medium scratch removal through hologram elimination in one step.

PERFORMANCE

BATTERY VOLTAGE	18 V (TDS)
BATTERY CAPACITY	2.5 / 5.0 / 8.0 Ah (TDS)
MAX. SUPPORT PLATE	150 mm (TDS)
POLISHING STROKE	8 mm (TDS)
NO-LOAD SPEED	225 – 700 rpm (TDS)
ORBIT RATE (NO LOAD)	2,700 – 8,700 rpm (TDS)
SOUND PRESSURE	76 dB(A) (TDS)
VIBRATION	5 m/s ² (TDS)
WEIGHT (NO BATTERY)	2.0 kg (TDS)

APPLICATION & PHYSICAL

DIMENSIONS	388 × 125 × 126 mm (TDS)
DRIVE	Forced rotation + random-orbital (TDS)
CONTROLS	Continuous speed trigger + bilateral speed wheel (TDS)
APPLICATIONS	Automotive, maritime, aviation (TDS)

OVERVIEW

FLEX XCE 8 150 18-EC cordless eccentric with forced rotation. CDC constant electronics and brushless motor deliver corded-class power for medium defects and hologram removal.

DIRECTIONS

1. Install an 18 V pack and the cushioned special hook-and-loop pad.
2. Select speed via the detent wheel; use soft-start trigger.
3. Work with forced-drive pressure appropriate to the pad — monitor heat.
4. Remove battery before pad changes.

SAFETY SNAPSHOT

CORDLESS POWER TOOL — EYE/HEARING PROTECTION

Follow FLEX operator manual. Use only approved FLEX 18 V batteries and chargers.

PLATFORM	18 V FLEX
STROKE	8 mm forced

Manufacturer SDS URL not retrieved for this article.

SOURCES

1. Manufacturer tech data / product information — https://hub.flex-tools.com/_f/76e/76e995ffc48eac90c82ee8c04ebd569fa8a78d4/DB_MA_532646.pdf
2. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailsupply.com/products/flex-xce-8-125-18-0-polisher-set>
3. Mapping note — MDSC title is XCE 8-125 18.0; current manufacturer sheet is XCE 8 150 18-EC (8 mm stroke). Family-level specs used; pad diameter listed as manufacturer publishes (150 mm).
4. Omissions — SDS not applicable / not retrieved.; MDSC title references XCE 8-125; manufacturer current TDS is XCE 8 150 18-EC (150 mm support plate).