



FLEX · FLEX POWER TOOLS · POLISHERS

PE 150 18-EC SET

18 V CORDLESS ROTARY · ORDER FAMILY PE 150 18-EC

SKU

459.569

DEFAULT TITLE

18 V cordless rotary polisher set for deep scratch removal and heavily weathered paint — CDC constant electronics hold speed under load.

PERFORMANCE

BATTERY VOLTAGE	18 V (TDS)
BATTERY CAPACITY	2.5 / 5.0 / 8.0 Ah (TDS)
MAX. SUPPORT PLATE	150 mm (TDS)
NO-LOAD SPEED	550 – 1,800 rpm (TDS)
SOUND PRESSURE	72 dB(A) EN 60745 (TDS)
VIBRATION	2.3 m/s ² EN 60745 (TDS)
WEIGHT (NO BATTERY)	2.1 kg (TDS)

APPLICATION & PHYSICAL

DIMENSIONS	407 × 72 × 108 mm (TDS)
MOTOR	Brushless with EMS (TDS)
CONTROLS	Continuous speed trigger + speed wheel with detents (TDS)
SET NOTE	Manufacturer set includes cushioned M14 pad, rapid charger, (2) 18 V packs (TDS) — confirm MDSC kit contents on catalog page

OVERVIEW

FLEX PE 150 18-EC cordless rotary polisher. Manufacturer rates it as powerful as a corded polisher across the battery life, with CDC constant electronics and a newly developed low-noise gearbox.

DIRECTIONS

- 1 Install a charged 18 V FLEX pack and an M14 rotary backing pad.
- 2 Use the speed wheel and trigger for a gentle start; lock on only for continuous runs.
- 3 Keep the flat gear head close to the panel; work controlled sections.
- 4 Remove the battery before pad changes.

SAFETY SNAPSHOT

CORDLESS POWER TOOL — EYE/HEARING PROTECTION

Follow FLEX operator manual. Use only approved FLEX 18 V batteries and chargers.

PLATFORM 18 V FLEX

WEIGHT W/O BATT. 2.1 kg

Manufacturer SDS URL not retrieved for this article.

SOURCES

1. Manufacturer tech data / product information — https://hub.flex-tools.com/_f/173/173015855da4f78d35d52ba201268964c12763e2/DB_MA_533019.pdf
2. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailssupply.com/products/flex-cordless-rotary-polisher-pe-150-18-0-ec>
3. Mapping note — Manufacturer product data sheet PDF (DB_MA_533019).
4. Omissions — SDS not applicable / not retrieved for this power tool.