



KOCH CHEMIE · KOCH-CHEMIE MARINE · COMPOUNDS & POLISHES

GELCOAT ONE CUT

HIGH-GLOSS POLISHING COMPOUND WITH SEALANT FOR GELCOATS AND BOAT PAINTS

SKU

509001US

1 LITER

1-step machine polish for all gelcoat and boat paint colors for the permanent removal of polishing haze, holograms and scratches with a simultaneous sealing effect. Gelcoat One Cut is economical, easy to polish and easy to wipe off and therefore has an optimum ratio of abrasiveness and gloss for economical and effec...

PERFORMANCE

ROLE	Polish
SURFACES / AREAS	Removal of polishing haze, holograms and scratches with a simultaneous sealing effect on gelcoats and boat paints
PH	8.2 (SDS)
APPEARANCE	Orange · Characteristic (SDS)
DENSITY	1.06 g/cm ³ (SDS)
SOLUBILITY	Mixable (SDS)

APPLICATION & PHYSICAL

METHOD	Can be applied using an eccentric polishing machine.
VOC	< 0,1 % (SDS)
TRANSPORT	Not regulated for transport (SDS §14)
WARNINGS (PI)	Shake before use. Check for material compatibility before use. Do not use on hot surfaces. Protect from frost and excessive heat. Do not use on unpainted plastics and rubber
MDSC SIZES	1 liter (509001US)

OVERVIEW

1-step machine polish for all gelcoat and boat paint colors for the permanent removal of polishing haze, holograms and scratches with a simultaneous sealing effect. Gelcoat One Cut is economical, easy to polish and easy to wipe off and therefore has an optimum ratio of abrasiveness and gloss for economical and effective work in marine refinishing. In addition, the polish produces a brilliant and durable high-gloss finish even on difficult, dark colors. Contains carnauba wax and non-volatile silicones and thus protects against chalking and weathering. SDS signal word: Warning.

DIRECTIONS

- 1 Can be applied using an eccentric polishing machine.
- 2 Spread 5 pea-sized drops on a suitable polishing pad (Micro Cut Pad hard) and work in a crosswise motion.
- 3 Spread the product on the surface at low speed and then process at the highest speed.
- 4 Buff out the polish and remove any remaining polish with a Polish & Sealing Towel.
- 5 Subsequent sealing is not necessary due to the wax components contained in the product.
- 6 PI warnings: Shake before use. Check for material compatibility before use. Do not use on hot surfaces. Protect from frost and excessive heat. Do not use on unpainted plastics and rubber

SAFETY SNAPSHOT

WARNING

Skin Sens. 1 · H317-May cause an allergic skin reaction. · H066-Repeated exposure may cause skin dryness or cracking. · EUH066-Repeated exposure may cause skin dryness or cracking.

APPEARANCE	Orange · Characteristic
PH / DENS.	8.2 · 1.06 g/cm ³
TRANSPORT	Not regulated for transport (SDS §14)
VOC	< 0,1 %

Manufacturer SDS — Koch-Chemie Gelcoat One Cut →

SOURCES

1. Manufacturer Product Information (Koch-Chemie) — https://www.koch-chemie.com/pdf/datasheet/Gelcoat_One_Cut_en.pdf
2. Manufacturer SDS (Koch-Chemie Gelcoat One Cut) — https://media.koch-chemie.com/pdf/SDBL/Gelcoat_One_Cut_Art_509999_509999_0006_EN.pdf
3. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailssupply.com/products/koch-chemie-gelcoat-one-cut>