



RUPES · BIGFOOT · COMPOUNDS & POLISHES

MARINE XP-900 POLYMER SPRAY SEALANT

POLYMER SPRAY SEALANT · UP TO 3 MONTHS (MFR)

SKU

9.XP900/6

Versatile spray-on marine sealant for gelcoat, metal, glass, vinyl, and paint — up to 3 months durability; can top XP-700.

PERFORMANCE

ROLE	Polymer spray sealant (mfr)
DURABILITY	Up to 3 months; reapply every 1–3 months (mfr)
SURFACES	Gelcoat, metal, glass, vinyl, painted surfaces (mfr)
APPEARANCE	Whitish liquid (SDS)
DENSITY	0.996 g/cm ³ ISO 2811 (SDS)
FLASH POINT	> 95 °C ASTM D3278 (SDS)
VISCOSITY	5–8 mm ² /s ISO 2555 (SDS)

APPLICATION & PHYSICAL

APPLICATION	Spray-on, wipe-off; usable on wet surfaces as drying aid (mfr)
TOPPER	Can extend durability of XP-700 (mfr)
NOT RECOMMENDED	Paint-application environments (mfr)
MDSC SKU	9.XP900/6

OVERVIEW

RUPES Marine XP-900 offers up to 3 months of UV protection, high gloss, and hydrophobic finish. Easy spray-on wipe-off; also usable wet as a drying aid. Suitable across gelcoat, metal, glass, vinyl, and painted surfaces.

DIRECTIONS

1. Shake and spray onto clean surface (or use as drying aid on wet surface).
2. Wipe to a clear finish.
3. Reapply every 1–3 months or as a topper over XP-700.
4. Do not use in paint-application environments.

SAFETY SNAPSHOT

AQUATIC ACUTE 1 H400 (SDS)

Follow manufacturer SDS. English SDS available on [rupes.com](https://www.rupes.com/msds/) MSDS index.

PHYSICAL STATE	Liquid (SDS)
COLOUR	Whitish (SDS)
DENSITY	0.996 g/cm ³ (SDS)

Manufacturer SDS — RUPES Marine XP-900 Polymer Spray Sealant

→

SOURCES

1. Manufacturer source — <https://www.rupes.com/product/marine-xp-900-polymer-spray-sealant/>
2. Manufacturer SDS — https://www.rupes.com/msds/2023/9.XP900/9.XP900_ENGLISH_REV1_2025_atp18.pdf
3. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailssupply.com/products/rupes-marine-xp-900-polymer-sprayer-sealant>
4. Mapping note — Marine brochure + product page + English SDS.
5. Document type — product_page