



AUTOFIBER · AUTOFIBER.COM · DECONTAMINATION

HOLEY CLAY DECON MITT

HOLEY CLAY · PERFORATED DECON MITT · 8.5" × 6"

SKU

CLAY-P-MITT-1

Perforated fine-grade clay mitt with flow-through holes (mfr).

PERFORMANCE

TYPE	Perforated clay decon mitt (mfr)
SIZE	8.5" × 6" (mfr)
GRADE	Fine grade — minimal paint damage (mfr)
FEATURE	Flow-through holes flush debris (mfr)

OVERVIEW

Holey Clay mitt uses perforated fine-grade clay so debris flushes through while decontaminating paint. Break in on glass with lube before paint work (mfr).

DIRECTIONS

- 1 First use: scrub on glass with lubrication to break in clay.
- 2 Keep mitt and paint wet with clay lube; work panel by panel.
- 3 Rinse mitt frequently; discard if clay is heavily contaminated or torn.

APPLICATION & PHYSICAL

MDSC SKU	CLAY-P-MITT-1
PREP	Break in on glass with lubrication first use (mfr)
LUBE	Continuous clay lube on mitt and paint (mfr)

SAFETY SNAPSHOT

CLAY DECON ARTICLE — USE WITH CLAY LUBRICANT; AVOID DRY CLAY ON PAINT

Not a chemical SDS article. Follow clay-lube product SDS. Do not clay dry.

SIZE	8.5" × 6"
GRADE	Fine
FORM	Mitt

Manufacturer SDS not retrieved for this article (towels/tools are articles — SDS often N/A) or see Autofiber downloads / local archive.

SOURCES

1. Manufacturer source — <https://www.autofiber.com/products/holey-clay-mitt-perforated-decon-mitt-9x6>
2. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailssupply.com/products/autofiber-holey-clay-decon-mitt>
3. Document type — product_page