



AUTOFIBER · AUTOFIBER.COM · DECONTAMINATION

HOLEY CLAY PERFORATED DECON TOWEL

HOLEY CLAY · PERFORATED TOWEL · ~10" × 10"

SKU

CLAY-P-TOWEL10-1

Thin perforated clay towel that conforms to contours (mfr).

PERFORMANCE

TYPE	Perforated clay decon towel (mfr)
SIZE (MDSC/TITLE)	10" class (MDSC 1-pack; mfr Holey Clay Towel)
GRADE	Fine grade (mfr)
FEATURE	Flow-through holes; thin/compact (mfr)

OVERVIEW

Holey Clay perforated towel lifts and flushes contaminants through flow-through holes while staying thin enough to follow contours. Break in on glass with lube (mfr).

DIRECTIONS

- 1 Break in on glass with clay lubricant.
- 2 Keep towel and paint lubricated; wipe/scrub gently.
- 3 Rinse often; replace when clay is spent.

APPLICATION & PHYSICAL

MDSC SKU	CLAY-P-TOWEL10-1
PREP	Break in on glass with lube (mfr)
LUBE	Continuous lubrication (mfr)

SAFETY SNAPSHOT

CLAY DECON ARTICLE — NEVER USE DRY; FOLLOW CLAY-LUBE SDS

Not a chemical SDS article. Use adequate lubrication.

FORM	Towel
GRADE	Fine

Manufacturer SDS not retrieved for this article (towels/tools are articles — SDS often N/A) or see Autofiber downloads / local archive.

SOURCES

1. Manufacturer source — <https://www.autofiber.com/products/holey-clay-towel-perforated-decon-towel-10x10>
2. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailsupply.com/products/holey-clay-towel-perforated-decon-towel-1-pack>
3. Omissions — Exact printed dimensions beyond MDSC 10" class — confirm on pack if needed.
4. Document type — product_page