



FLITZ · SEALANTS

FLITZ CERAMIC SPRAY SEALANT

SPRAY-ON NANO-CERAMIC SEALANT · UP TO 1 YEAR PROTECTION

SKU

CS 02906

Easy spray-on nano-ceramic sealant that forms a slick, water-resistant barrier to repel dirt, water, and contaminants — hydrophobic protection lasting up to one year with proper care (flitz.com product page).

PERFORMANCE

ROLE	Hand-applied / spray ceramic sealant (mfr product page / US SDS recommended use)
DURABILITY (MFR)	Up to 1 year with proper care (mfr product page)
FINISH	Hydrophobic, ultra-slick, glossy; streak-free when buffed immediately (mfr product page)
SURFACES (YES)	Clear coats, paint, fiberglass, aluminum, diamond plate; granite, marble, glass, stainless, plastics; toolboxes, RV exteriors, motorcycles, chrome (mfr product page)
NOT FOR (MFR)	NOT for floors — creates an extremely slick surface (mfr product page)
COVERAGE (MFR)	8 oz ≈ 1,100 sq ft; 16 oz ≈ 2,200 sq ft; 32 oz ≈ 4,400 sq ft; gallon ≈ 17,600 sq ft (mfr product page)

APPLICATION & PHYSICAL

METHOD	Spray onto clean, dry surface; buff immediately with microfiber — do not let dry (mfr product page)
SECOND COAT	Apply after 48 hours for maximum durability (mfr product page)
DILUTION	Ready-to-use spray — no dilution published
PACK (MDSC)	Catalog SKU CS 02906 (space in SKU); maps to mfr CS02906 family (older SDS ID list)
MDSC BARCODE CHECK	065925029062 — aligns with CS02906 family numbering

OVERVIEW

Easy spray-on nano-ceramic sealant that forms a slick, water-resistant barrier to repel dirt, water, and contaminants — hydrophobic protection lasting up to one year with proper care (flitz.com product page).

DIRECTIONS

- 1 Start with a clean, dry surface (mfr product page).
- 2 Spray Flitz Ceramic Sealant directly onto the surface (mfr product page).
- 3 Buff immediately with a Flitz Microfiber Cloth — do not let the sealant dry (mfr product page).
- 4 For maximum durability, apply a second coat after 48 hours (mfr product page).
- 5 Do not use on floors (mfr product page).

SAFETY SNAPSHOT

WARNING (MFR US SDS 4/11/2023)

Skin irritation Cat. 2 (H315); Eye irritation Cat. 2A (H319). Wash hands after handling; wear protective gloves and eye protection (mfr US SDS §2).

APPEARANCE	White liquid (mfr US SDS §9)
PH	6.5 – 7.5 (mfr US SDS §9)
BOILING POINT	100 °C (mfr US SDS §9)
FLASH POINT	> 100 °C (mfr US SDS §9)
RELATIVE DENSITY	0.95 – 1.05 (mfr US SDS §9)
SOLUBILITY	Soluble in water (mfr US SDS §9)
ODOR	Faint (mfr US SDS §9)

Manufacturer SDS — Ceramic Sealant →

SOURCES

1. Manufacturer tech data / product information — <https://www.flitz.com/flitz-ceramic-sealant/>
2. Manufacturer SDS (Ceramic Sealant) — https://www.flitz.com/content/Ceramic%20Sealant_US%20SDS.pdf
3. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailssupply.com/products/flitz-ceramic-spray-coating>
4. Mapping note — MDSC SKU 'CS 02906' (space) maps to mfr CS02906 on older SDS ID list and Ceramic Sealant product family on flitz.com.
5. Omissions — VOC % not published on manufacturer SDS — omitted; Standalone TDS/sell-sheet PDF not linked on ceramic product page — coverage/durability from product page; Exact bottle size for MDSC CS 02906 not labeled on mfr default SKU selector — omitted pack volume rather than guessing; Older 2021 SDS (not classified) archived; 2023 US SDS used for hazard/phys