



FLEX · FLEX POWER TOOLS · POLISHERS

24V RANDOM ORBITAL POLISHER KIT

CORDLESS FREE-SPIN DA · MODEL FX3321-2C

SKU

FX3321-2C

DEFAULT TITLE

Cordless 24V random-orbital polisher for hologram-free finishing with up to 4,350 RPM and 8,700 OPM.

PERFORMANCE

DRIVE TYPE	Random orbital / free-spin (mfr)
BATTERY PLATFORM	FLEX 24V (mfr)
NO-LOAD SPEED	1,350 – 4,350 RPM (mfr)
ORBIT	0.59 in / 15 mm (mfr)
ORBIT RATE (NO LOAD)	2,700 – 8,700 OPM (mfr)
MOTOR	Brushless (mfr)
MAX. POLISHING PAD	6 in (mfr)
TOOL WEIGHT	4.6 lbs (mfr)

APPLICATION & PHYSICAL

KIT INCLUDES	Polisher, (2) 5.0Ah batteries, 160W fast charger, 5" & 6" backing pads, Allen key, soft bag (mfr)
SPEED CONTROL	11-speed dial + variable trigger (mfr)
TOOL SIZE	15.2 × 3.8 × 5.4 in (mfr)
USE CASE	Finishing without hologram formation (mfr)

OVERVIEW

FLEX 24V cordless random-orbital polisher kit for finishing work. Free-spinning drive for hologram-free results with constant-speed electronics and vibration control.

DIRECTIONS

1. Install the matching DA backing pad and a finishing foam or microfiber pad.
2. Start at a moderate speed; keep the pad flat and overlapping passes.
3. Use light to moderate pressure — free-spin tools finish best without forcing the orbit.
4. Wipe and inspect under proper lighting before final protection.

SAFETY SNAPSHOT

POWER TOOL — EYE/HEARING PROTECTION

Follow FLEX operator manual. Disconnect battery before pad changes.

PLATFORM	24V FLEX
ORBIT	15 mm

Manufacturer SDS URL not retrieved for this article.

SOURCES

1. Manufacturer tech data / product information — <https://www.flexpowertools.com/random-orbital-polisher-fx3321/>
2. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailsupply.com/products/flex-24v-random-orbital-polisher-kit-fx3321-2c-pre-order>
3. Mapping note — Official FLEX US product page specs.
4. Omissions — SDS not published for this power tool; consult operator manual.