



JESCAR · SEALANTS

JESCAR ULTRA LOCK PLUS POLYMER SEALANT

SIO₂-INFUSED POLYMER / CERAMIC HYBRID SEALANT

SKU

J-UL98P

16 OZ.

32 OZ.

128 OZ.

J-UL98Q

J-UL98G

Hybrid polymer sealant with ceramic SiO₂ technology for over 6 months of high-gloss protection, extreme water beading, UV resistance, and a slick finish; developed from Power Lock Plus chemistry (jescarfinishing.com).

PERFORMANCE

ROLE	SiO ₂ -infused polymer / ceramic hybrid paint sealant (mfr product page)
DURABILITY (MFR)	Over 6 months of UV and environmental protection when applied correctly (mfr product page)
KEY FEATURES	Extreme water beading · deep gloss · slick finish · stain/etch resistance (mfr product page)
SURFACES (MFR)	Paint, glass, lights, metal / clear coat; silicone-free and body-shop safe (mfr product page)
VS POWER LOCK PLUS	Adds SiO ₂ for longer protection, better beading, and increased slickness (mfr product page FAQ)

APPLICATION & PHYSICAL

METHOD	Hand (foam/microfiber applicator) or DA / machine polisher (mfr product page)
LAYERING	Optional second coat after 3 hours (mfr product page)
CONDITIONS	Work in shade on a cool surface (mfr product page)
PACK SIZES (CATALOG)	16 oz. · 32 oz. · 128 oz.

OVERVIEW

Hybrid polymer sealant with ceramic SiO₂ technology for over 6 months of high-gloss protection, extreme water beading, UV resistance, and a slick finish; developed from Power Lock Plus chemistry (jescarfinishing.com).

DIRECTIONS

- 1 Work in shade on a cool surface (mfr product page).
- 2 Shake bottle well (mfr product page).
- 3 Apply a thin, even layer using a soft applicator or DA polisher (mfr product page).
- 4 Allow to haze, then buff off with a microfiber towel (mfr product page FAQ).
- 5 Optional second layer after waiting 3 hours for enhanced durability (mfr product page).

SAFETY SNAPSHOT

DANGER — ASPIRATION TOX. 1 · EYE IRRIT. 2 · SKIN IRRIT. 2 (MFR SDS §2)

Asp. Tox. 1 H304 · Eye Irrit. 2 H319 · Skin Irrit. 2 H315 (mfr SDS §2). Keep container tightly closed. Wear protective gloves/eye protection.

PHYSICAL STATE Cream liquid · Light Blue · Slight odor (SDS §9)
PH 7 (SDS §9)
FLASH POINT 200°F (SDS §9)
VOC 0% (SDS §9)
WATER SOLUBILITY Insoluble (SDS §9)

Manufacturer SDS — Ultra Lock Plus →

SOURCES

1. Manufacturer tech data / product information — <https://jescarfinishing.com/products/jescar-ultra-lock>
2. Manufacturer SDS (Ultra Lock Plus) — https://cdn.shopify.com/s/files/1/0050/0950/6339/files/Jescar_Ultra_Lock_SDS.pdf?v=1641404765
3. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailssupply.com/products/jescar-ultra-lock-plus-polymer-sealant>
4. Omissions — Specific gravity / relative density not published as determined on SDS §9; Exact haze time minutes not published as a single number on product page (FAQ: let it haze)