



MENZERNA · COMPOUNDS & POLISHES

MENZERNA SUPER FINISH POLISH 3500

HIGH-GLOSS HOLOGRAM REMOVER · FINISH POLISH

SKU

M-3500Q

1 LITER

Versatile high-gloss finish polish that removes polishing marks, micro-scratches, and holograms for a brilliant deep shine; dark/grey color makes it especially suitable for black and other dark coats (mfr product page / EN TDS).

PERFORMANCE

ROLE	Finish / high-gloss anti-hologram polish (mfr product page / EN TDS)
CUT / GLOSS (MFR)	Cut 3 · Gloss 10 (mfr product page / EN TDS)
REMOVES	Polishing marks, micro-scratches, holograms, gray smears / swirls (mfr product page / EN TDS)
SILICONE-FREE	Yes — silicone-free (mfr product page)
BEST FOR (MFR)	Black and other dark coats; also listed among polishes ideal for sticky paint (mfr product page FAQ)

APPLICATION & PHYSICAL

METHOD	Orbital (upper rotational speed range) or by hand with light circular pressure; Soft Cut Foam Pad (mfr product page / EN TDS)
SPEED (TDS)	1,200–2,000 rpm (EN TDS)
STORAGE (TDS)	5–30 °C; avoid frost and direct sunlight (EN TDS)
DENSITY (TDS)	1.1 kg/l (EN TDS)
PACK SIZES (CATALOG)	1 liter

OVERVIEW

Versatile high-gloss finish polish that removes polishing marks, micro-scratches, and holograms for a brilliant deep shine; dark/grey color makes it especially suitable for black and other dark coats (mfr product page / EN TDS).

DIRECTIONS

- 1 Clean the surface thoroughly (mfr product page / EN TDS).
- 2 Shake the bottle and apply polish to the Soft Cut Foam Pad — about 3 (ø95 mm) to 7 (ø180 mm) pea-sized drops depending on pad size (mfr product page / EN TDS).
- 3 Prefer an orbital polisher with the cross-coating method; hand application with Hand Polishing Applicator is also published (mfr product page).
- 4 Exert light and even pressure and work at a consistently high rotational speed (product page); EN TDS also notes strong even pressure at consistently low speed — follow the published guidance for your machine type (mfr product page / EN TDS).
- 5 Work until only a slightly transparent/oily film remains, then remove residue with a Premium microfiber cloth (mfr product page / EN TDS).
- 6 Seal with a Menzerna Protection product if desired (mfr product page / EN TDS).

SAFETY SNAPSHOT

NOT CLASSIFIED UNDER GHS (MFR SDS §2)

GHS label elements / signal word / hazard statements: Void — product not classified according to GHS on SDS (mfr SDS §2). Keep out of reach of children.

PHYSICAL STATE	Viscous · Grey · Characteristic odor (SDS §9)
PH (20 °C)	>7 (SDS §9)
FLASH POINT	>100 °C / >212 °F (SDS §9)
DENSITY (20 °C)	1.1 g/cm ³ (SDS §9); 1.1 kg/l (EN TDS)
VOC	12.4% · 691.6 g/l (SDS §9)
WATER SOLUBILITY	Not miscible or difficult to mix (SDS §9)

Manufacturer SDS — Super Finish 3500 —

SOURCES

1. Manufacturer tech data / product information — https://www.menzerna.com/fileadmin/ns_theme_menzerna/Dokumente/Technische_Datenblaetter/Autopolituren/EN/TDB_SF3500_22911_20231113_EN.pdf
2. Manufacturer product page — <https://www.menzerna.com/car-care/car-polish/products/details/super-finish-3500>
3. Manufacturer SDS (Super Finish 3500) — <https://menzernausa.com/wp-content/uploads/2016/04/3500.pdf>
4. MDSC catalog for name / SKU / image / pack sizes only — <https://marinedetailsupply.com/products/menzerna-super-finish-polish-3500>
5. Mapping note — Catalog title 'Super Finish Polish 3500' maps to manufacturer Super Finish 3500 / SF 3500 (article 22911). SDS from official Menzerna USA hub (menzernausa.com).
6. Omissions — Dilution ratio not published (ready-to-use polish); Numeric grit removal claim not published on SF 3500 TDS (hologram / micro-scratch removal only)