



GTECHNIQ · COATINGS & SEALANTS

RINSE-ON CERAMIC

GTECHNIQ MARINE SEALANT

SKU

MRC 0.5

500 ML

UP TO 3 MO

Sprayable rinse-on ceramic sealant. Bonds on a wet gel coat during the final rinse. No buffing between steps.

PERFORMANCE

TYPE	Sprayable ceramic sealant / rinse-on coating (SDS: boat coating)
ROLE	Fast ceramic protection between full coating applications; also a drying aid (FAQ)
DURABILITY	Kit FAQ: months of water beading/UV; reapply after each wash or when beading fades. Category page: 3 months. Refill page: up to 3 months.
SURFACES	Gel coat, fiberglass, painted surfaces; also metal trim and wheels (FAQ). Avoid non-skid (slickness).
FINISH	Water beading, high gloss, UV protection; optically clear / non-yellowing (refill page)
WET APPLY	Formulated for wet-surface rinse-off. Not for dry-surface application (FAQ).

APPLICATION

PREP	Wash thoroughly and rinse; keep the exterior wet
APPLY	Light mist, one panel at a time, spray bottle or pump sprayer
RINSE	Rinse immediately so the sealant spreads and bonds; let water sheet
DRY	MF2 Zero Scratch Microfibre Drying Towel
CONDITIONS	Avoid direct sunlight or hot surfaces
DENSITY	1–1.03 relative (SDS)
STORAGE	Cool, dry place (product page)

OVERVIEW

Gtechniq Rinse-On Ceramic is a sprayable sealant that applies ceramic protection during the final rinse on a wet gel coat. The kit product page describes water beading, gloss, and UV protection without buffing between steps. Durability is published three ways: kit FAQ (months; reapply after each wash), sealants category (3 months), and the refill product page (up to 3 months). Surfaces: gel coat, fiberglass, paint; avoid non-skid. Manufacturer does not publish coverage, VOC, pH, or hardness.

DIRECTIONS

- 1 Shake spray bottle well before use and wear gloves.
- 2 Wash the boat thoroughly and rinse.
- 3 While the exterior is still wet, spray directly onto gel coat, one panel at a time.
- 4 Apply a light mist with the spray bottle or a pump sprayer.
- 5 Rinse immediately with water to spread and bond the sealant.
- 6 Allow rinse water to sheet off. Dry with an MF2 Zero Scratch Microfibre Drying Towel.
- 7 Avoid direct sunlight or hot surfaces. Store cool and dry.

SAFETY SNAPSHOT

NONE

Not classified (GHS US). P102 Keep out of reach of children.

APPEARANCE	Colorless liquid
ODOR	Not a single published odor (SDS: component odours)
DENSITY	1–1.03 relative
FLASH POINT	>100 °C / >212 °F
FLAMMABILITY	Non flammable (SDS)
TRANSPORT	Not regulated (DOT / IMDG / IATA)

SDS MRC US v1.0 — 07/01/2020

SOURCES

1. Manufacturer product page (kit) — <https://gtechniq.com/shop/marine/coating-sealants-marine/rinse-on-ceramic/>
2. Manufacturer marine sealants category (3-month durability) — <https://gtechniq.com/product-category/marine/coating-sealants-marine/>
3. Manufacturer refill page (up to 3 months / optically clear copy) — <https://gtechniq.com/shop/marine/coating-sealants-marine/rinse-on-ceramic-refill/>
4. SDS MRC US v1.0, issue 07/01/2020 — https://gtechniq.com/wp-content/uploads/2023/05/MRC_US.pdf
5. MDSC catalog for name / SKU / image / size only — <https://marinedetailsupply.com/products/gtechnic-rinse-on-ceramic>