



DITEC MARINE PRODUCTS · COATINGS & SEALANTS

## PROTEC QUICK COATING

PAINT / GELCOAT HYDROPHOBIC MAINTENANCE SPRAY

SKU

**PG-PRTC-QC02**

**24 OZ**

**60-90 DAY**

Fast maintenance spray that adds a protective, hydrophobic, glossy finish on painted and gelcoat surfaces. Standalone for several months, or over PROTEC 1 / other coatings for multi-year systems. Manufacturer also lists a gallon size.

### PERFORMANCE

|                      |                                                                                                       |
|----------------------|-------------------------------------------------------------------------------------------------------|
| <b>ROLE</b>          | Quick detailer / maintenance coating for paint, gelcoat, and metal                                    |
| <b>DURABILITY</b>    | Protection on paint/gelcoat for 60-90 days                                                            |
| <b>INTERVAL</b>      | Minimum one application every 90 days (3 months); more often for gloss if desired                     |
| <b>WITH PROTEC 1</b> | Recommended in addition to PROTEC 1 or other coatings for multi-year protection                       |
| <b>BENEFITS</b>      | Dirt/grime/contamination resistance · hydrophobic · keeps coatings active · dry quick-detailer option |
| <b>PH</b>            | 5 (product page and SDS)                                                                              |
| <b>SOLUBILITY</b>    | 100% in water (completely soluble)                                                                    |
| <b>MFR. SIZES</b>    | 24 oz trigger spray (this SKU) · gallon (PG-PRTC-QC03)                                                |

### APPLICATION & CURE

|                    |                                                                                                              |
|--------------------|--------------------------------------------------------------------------------------------------------------|
| <b>SURFACES</b>    | Paint/gelcoat and metal                                                                                      |
| <b>BEST METHOD</b> | Spray onto a washed and dried surface in sections; wipe with a dry microfiber (longest-lasting, streak-free) |
| <b>ALSO LISTED</b> | Spray on, rinse off for a super-quick application · can be used dry as a quick detailer                      |
| <b>CONDITIONS</b>  | Do not use on hot surfaces · avoid direct sunlight · eye protection and nitrile gloves                       |
| <b>PREP WASH</b>   | Wash thoroughly with DITEC Boat Soap; clean sponge and bucket                                                |
| <b>APPEARANCE</b>  | Liquid (product page) · SDS: green liquid, perfume odor                                                      |
| <b>DENSITY</b>     | 0.98 g/cm <sup>3</sup> (SDS)                                                                                 |

### OVERVIEW

DiTEC PROTEC Quick Coating is a water-soluble maintenance spray (pH 5) that quickly adds hydrophobic gloss and protection against dirt, grime, and paint-contamination degradation. Product page: 60-90 days on paint/gelcoat; use alone for several months or over PROTEC 1. Two application modes are published: spray-on/rinse-off, and spray-on-dry/wipe (stated as longest lasting).

### DIRECTIONS

- 1 Do not use on hot surfaces. Avoid direct sunlight. Wear eye protection and nitrile gloves.
- 2 Wash the boat thoroughly with DiTEC Boat Soap. Use a clean sponge and bucket.
- 3 For longest-lasting protection: spray onto a washed and dried surface, working in sections. Wipe off with a dry microfiber cloth for a streak-free finish.
- 4 Product page also lists a spray-on, rinse-off method for a super-quick application, and dry use as a quick detailer.
- 5 Repeat at least every 90 days (3 months). May be used more frequently for a streak-free glossy finish.

### SAFETY SNAPSHOT

#### WARNING

Flam. Liq. 3 (H226) · Aquatic Chronic 3 (H412) · EUH208 Contains 1,2-benzisothiazol-3(2H)-one; may produce an allergic reaction. UFI QST5-TG9Y-U10F-16HM.

|                     |                                                                     |
|---------------------|---------------------------------------------------------------------|
| <b>APPEARANCE</b>   | Green liquid · perfume odor (SDS)                                   |
| <b>PH / DENSITY</b> | 5 · 0.98 g/cm <sup>3</sup>                                          |
| <b>FLASH POINT</b>  | 42°C (SDS)                                                          |
| <b>TRANSPORT</b>    | UN1993 Flammable liquid, n.o.s. (propan-2-ol), 3, III · Ltd Qty 5 L |
| <b>HMIS</b>         | Not published on manufacturer SDS                                   |

**SDS PROTEC Quick Coating rev 1.0** → 29/11/2022

### SOURCES

1. Manufacturer product page — <https://ditecmarineproducts.com/products/protect-quick-coating>
2. Manufacturer SDS (Protect Quick Coating, 29/11/2022, product no. PG-PRTC-QC02) — [https://cdn.shopify.com/s/files/1/0569/2378/3325/files/Protect\\_Quick\\_Coating-SDS-11.29.22.pdf?v=1711381627](https://cdn.shopify.com/s/files/1/0569/2378/3325/files/Protect_Quick_Coating-SDS-11.29.22.pdf?v=1711381627)
3. Manufacturer SDS index — <https://ditecmarineproducts.com/pages/safety-data-sheet>
4. MDSC catalog for name / SKU / image / 24 oz size only — <https://marinedetailsupply.com/products/ditec-protect-quick-coating>