



STARKE YACHT CARE · WASH & MAINTENANCE

STARKE PURE CLEAN

REFILL KIT · PH-NEUTRAL BOAT SOAP

SKU

PURKIT

REFILL KIT

CHEM BOM

PUC16

16 OZ

PUC128

128 OZ JUG

Refill kit BOM: PUC16 (16 oz); PUC128 (128 oz jug). Weekly pH-neutral wash soap. Cleans without stripping waxes, polymer sealants, or ceramic coatings. Foam cannon or bucket.

PERFORMANCE

ROLE	Foundation of the Starke Clean System — weekly wash
PH	Neutral range (SDS 7–9); does not strip protection
SAFE ON	Waxes, polymer sealants (Hyper Hold Pro, Hydro Guard), ceramics
CERAMIC BOATS	Starke recommends Ultra Clean (SiO ₂) instead for coated hulls
BOOST	Add Simple Clean to raise alkalinity for black streaks / heavy soil
VOC	0% (SDS)

APPLICATION

METHOD	Foam cannon or bucket. Top to bottom. Microfiber mitt, straight lines. Rinse.
DILUTION	Not published as a ratio — concentrated; use a small amount
WHEN	Weekly maintenance regardless of protection system
SIZES	16 oz · 32 oz · 128 oz

OVERVIEW

Refill kit containing Pure Clean 16 oz bottle and 128 oz ultra-concentrated refill jug. Chemical specs below are the parent Pure Clean formula. Pure Clean is the weekly wash soap in the Starke Clean System. The pH-neutral formula (SDS 7–9) cleans marine surfaces without stripping waxes, polymer sealants, or ceramic coatings. Use it on boats running Hyper Hold Pro or Hydro Guard. For ceramic-coated boats (Repel Pro, Liquid Thor), Starke points to Ultra Clean. Add Simple Clean when you need more cut on black streaks or heavy contamination.

DIRECTIONS

- 1 Fill a foam cannon or wash bucket. Add a small amount of Pure Clean (concentrated; no published ratio).
- 2 Work top to bottom with a microfiber mitt in straight lines.
- 3 Rinse clean.
- 4 For extra cut on black streaks or heavy soil, add Simple Clean to the same wash.
- 5 Ceramic-coated boats: Starke recommends Ultra Clean in place of Pure Clean for weekly SiO₂ reinforcement.

SAFETY SNAPSHOT

WARNING		HMIS	1 H	0 F	0 P
Eye Irrit. 2B					
APPEARANCE	Blue viscous liquid				
ODOR	Coconut fragrance				
PH	7–9				
DENSITY	0.865				
BOILING	100°C / 212°F				
FLASH POINT	107°C / 225°F				
VOC	0%				
TRANSPORT	Not regulated				
SDS SYC-001 rev 1.1 → 10/16/2025					

SOURCES

1. Starke refill kit page — <https://starkeyachtcare.com/products/starke-pure-clean-kit>
2. Starke parent chemical product page — <https://starkeyachtcare.com/products/starke-pure-clean-boat-soap>
3. SDS SYC-001 rev 1.1, 10/16/2025
4. Refill kit — parent chemical SDS/TDS numbers apply.