



STARKE YACHT CARE · COATINGS & SEALANTS

STARKE REBOOT

GRAPHENE MAINTENANCE SPRAY

SKU

RBOOT8

8 OZ

GRAPHENE OXIDE

Graphene oxide spray sealant — standalone up to 12 months of graphene protection, or a maintenance booster for Liquid Kraken. Not interchangeable with Replenish (SiO₂).

PERFORMANCE

ROLE	Standalone graphene spray or Kraken booster
CHEMISTRY	Graphene oxide (not SiO ₂)
DURABILITY	Up to 12 months standalone
INTERVAL	9–12 months · 6 months heavy salt/harsh exposure
PAIR WITH	Liquid Kraken (after full decontamination)
DO NOT SWAP	Replenish is SiO ₂ for Repel/Thor systems

APPLICATION

PREP	Clean, fully decontaminated surface
APPLY	Light even spray — less is more
BOND	30–60 seconds, then buff clear
TOOLS	Two clean microfibers (work + buff)
SIZE	8 oz
CAUTION	Flammable — gloves, eye protection, ventilation

OVERVIEW

Reboot is a graphene oxide spray sealant that stands on its own — up to 12 months of hydrophobic performance, water-spot resistance, and clarity with no ceramic underneath required. It also refreshes Liquid Kraken between full recoats after proper decontamination. Reboot is graphene chemistry; Replenish is SiO₂ for Repel Pro / Liquid Thor — they are not interchangeable. Recommended every 9–12 months (every 6 months in heavy salt).

DIRECTIONS

- 1 Start with a clean, fully decontaminated surface. Contamination left in place blocks graphene oxide bonding.
- 2 Spray Reboot lightly and evenly — less is more. Work in with a clean microfiber.
- 3 Allow 30–60 seconds for the graphene oxide to bond, then buff to a clear finish with a second clean microfiber.
- 4 As a Kraken booster or standalone: reapply every 9–12 months (every 6 months in heavy saltwater / harsh exposure).
- 5 Flammable — gloves, eye protection, good ventilation; no ignition sources during application.

SAFETY SNAPSHOT

WARNING

HMIS

1
H

1
F

0
P

Flam. Liq. 3 · Asp. Tox. 1 · STOT SE 3 · Eye Irrit. 2 · Skin Irrit. 3 · Aquatic Chronic 4

APPEARANCE	Black liquid
ODOR	Ammonia-like — fruity
DENSITY	0.9297 g/cm ³
FLASH POINT	54°C / 129°F
BOILING	> 65°C / 149°F
TRANSPORT	UN1993 Flammable Liquid, N.O.S., 3, III

SDS SYC-021 rev 1.0 → 5/17/2022

SOURCES

1. Starke product page — <https://starkeyachtcare.com/products/starke-graphene-maintenance-spray>
2. SDS SYC-021 rev 1.0, 5/17/2022