



STARKE YACHT CARE · SEALANTS

STARKE REVOLUTION CLEANER WAX · POLYMER SEALANT

SKU

REV16

16 OZ

3-IN-1

REV32

32 OZ

REV128

128 OZ

Three-in-one cleaner wax with polymer sealant chemistry — not carnauba. Light oxidation, polish, and 3–6 months of marine protection in one pass.

PERFORMANCE

ROLE	3-in-1: clean light oxidation · polish · polymer seal
CHEMISTRY	Polymer sealant (not carnauba — carnauba fails ~105°F)
DURABILITY	3–6 months (product page). Older how-to: 1–3 months
COLOR	White cream — no dyes; safe on light gel coat / metals
SURFACES	Gel coat, marine paint, metal
CUT	How-to: micro-abrasive; DA + foam pad removes ~3000-grit marks

APPLICATION

MACHINE	Random orbital / dual-action (product page)
PAD	Foam or microfiber applicator; how-to: heavy polishing pad
SECTION	2' × 3' · thin even coat
DWELL	2–5 minutes, then buff clean
TO WATER	How-to: 24–48 h dry; 5–7 days before heavy cleaners
SIZES	16 oz · 32 oz · 128 oz

OVERVIEW

Revolution is called a cleaner wax, but the protection chemistry is a polymer sealant — carnauba begins failing near 105°F, which on a Florida deck can be mid-morning. One pass removes light oxidation, polishes, and seals. The cream is white by design (no dyes). Product-page durability is 3–6 months; the 2022 how-to listed 1–3 months. Use on well-maintained boats on a quarterly schedule or as a fast one-step job. Maintain with Hydrate or Replenish after washes.

DIRECTIONS

- For best results, chemically decontaminate first with Venom Water Spot Remover.
- Work 2' × 3' sections with a dual-action polisher and foam or microfiber pad. Apply a thin, even coat.
- Allow 2–5 minutes dwell. How-to: cycle 3–4 times like a polish to clear light defects.
- Buff residual with a clean microfiber.
- Keep off water 24–48 hours. Wait 5–7 days before heavy cleaners. Extend with Hydrate or Replenish after each wash.

SAFETY SNAPSHOT

DANGER

HMS

1
H

0
F

0
P

Asp. Tox. 1 · Skin Irrit. 3 · Repr. 2 · Aquatic Chronic 1

APPEARANCE	Off-white viscous liquid
ODOR	Sweet
PH	7–9
DENSITY	0.99 g/cm ³ @ 25°C
FLASH POINT	> 100°C / 212°F
BOILING	100°C / 212°F
TRANSPORT	Not regulated

SDS SYC-002 rev 1.0 → 3/3/2021

SOURCES

- Starke product page — <https://starkeyachtcare.com/products/reel-shine-starke-revolution-cleaner-wax>
- Starke how-to — <https://starkeyachtcare.com/blogs/news/how-to-use-the-starke-revolution-cleaner-wax>
- SDS SYC-002 rev 1.0, 3/3/2021